



S Line

S-Line series produced with superior STF quality standards; which can adapt to all kinds of terrain. Thanks to its special drip design, it reduces the possibilities of clogging to the minimum level and ensures an efficient and trouble-free irrigation.



S-LINE is produced for field crops.

- Thanks to its effective drip design against clogging works trouble free.
- It provides superior irrigation performance with homogeneous water and nutrient distribution even at low pressure.
- It is resistant to different factors (UV light, heat and soil creatures).



- It has been developed for trouble-free irrigation. Thanks to the materials used in its production, display high UV resistance and high resistance against pesticides, fertilizers and acids.
- Produced in a wide range of options, diameter (16-22-25mm), wall thickness (0.15-0.20-0.25-0.30-0.40mm), and different dripper options, suitable for every project is provided.

Dia 16 mm / 6 mil / 0,15 mm

Flow Rate	Code	Emitter Spacing	Maximum Length	Roll Length
1,6 lt/h	SL-16061016	10 cm	44 m	2000 m
	SL-16061516	15 cm	60 m	2500 m
	SL-16062016	20 cm	74 m	2500 m
	SL-16062516	25 cm	87 m	2500 m
	SL-16063016	30 cm	100 m	2500 m
	SL-16064016	40 cm	121 m	2500 m
2,2 lt/h	SL-16065016	50 cm	141 m	2500 m
	SL-16061022	10 cm	38 m	2000 m
	SL-16061522	15 cm	54 m	2500 m
	SL-16062022	20 cm	65 m	2500 m
	SL-16062522	25 cm	77 m	2500 m
	SL-16063022	30 cm	87 m	2500 m
3,5 lt/h	SL-16064022	40 cm	107 m	2500 m
	SL-16065022	50 cm	124 m	2500 m
	SL-16061035	10 cm	23 m	2000 m
	SL-16061535	15 cm	36 m	2500 m
	SL-16062035	20 cm	44 m	2500 m
	SL-16062535	25 cm	52 m	2500 m
3,5 lt/h	SL-16063035	30 cm	59 m	2500 m
	SL-16064035	40 cm	72 m	2500 m
	SL-16065035	50 cm	84 m	2500 m

Maximum working pressure: **1,0 Bar**
Recommended Filtration 130 Micron-120 Mesh

Dia 16 mm / 8 mil / 0,20 mm

Flow Rate	Code	Emitter Spacing	Maximum Length	Roll Length
1,6 lt/h	SL-16081016	10 cm	60 m	2000 m
	SL-16081516	15 cm	60 m	2300 m
	SL-16082016	20 cm	74 m	2300 m
	SL-16082516	25 cm	87 m	2300 m
	SL-16083016	30 cm	100 m	2300 m
	SL-16084016	40 cm	121 m	2300 m
2,2 lt/h	SL-16085016	50 cm	141 m	2300 m
	SL-16081022	10 cm	54 m	2000 m
	SL-16081522	15 cm	54 m	2300 m
	SL-16082022	20 cm	65 m	2300 m
	SL-16082522	25 cm	77 m	2300 m
	SL-16083022	30 cm	87 m	2300 m
3,5 lt/h	SL-16084022	40 cm	107 m	2300 m
	SL-16085022	50 cm	124 m	2300 m
	SL-16081035	10 cm	23 m	2000 m
	SL-16081535	15 cm	36 m	2300 m
	SL-16082035	20 cm	44 m	2300 m
	SL-16082535	25 cm	52 m	2300 m
3,5 lt/h	SL-16083035	30 cm	59 m	2300 m
	SL-16084035	40 cm	72 m	2300 m
	SL-16085035	50 cm	84 m	2300 m

Maximum working pressure: **1,1 Bar**
Recommended Filtration 130 Micron-120 Mesh

Dia 16 mm / 10 mil / 0,25 mm

Flow Rate	Code	Emitter Spacing	Maximum Length	Roll Length
1,6 lt/h	SL-16101516	15 cm	60 m	2000 m
	SL-16102016	20 cm	74 m	2000 m
	SL-16102516	25 cm	87 m	2000 m
	SL-16103016	30 cm	100 m	2000 m
	SL-16104016	40 cm	121 m	2000 m
	SL-16105016	50 cm	141 m	2000 m
2,2 lt/h	SL-16101522	15 cm	54 m	2000 m
	SL-16102022	20 cm	65 m	2000 m
	SL-16102522	25 cm	77 m	2000 m
	SL-16103022	30 cm	87 m	2000 m
	SL-16104022	40 cm	107 m	2000 m
	SL-16105022	50 cm	124 m	2000 m
3,5 lt/h	SL-16101535	15 cm	36 m	2000 m
	SL-16102035	20 cm	44 m	2000 m
	SL-16102535	25 cm	52 m	2000 m
	SL-16103035	30 cm	59 m	2000 m
	SL-16104035	40 cm	72 m	2000 m
	SL-16105035	50 cm	84 m	2000 m

Maximum working pressure: **1,3 Bar**
Recommended Filtration 130 Micron-120 Mesh

Dia 16 mm / 12 mil / 0,30 mm

Flow Rate	Code	Emitter Spacing	Boru serimi Length	Roll Length
1,6 lt/h	SL-16121516	15 cm	60 m	1700 m
	SL-16122016	20 cm	74 m	1700 m
	SL-16122516	25 cm	87 m	1700 m
	SL-16123016	30 cm	100 m	1700 m
	SL-16124016	40 cm	121 m	1700 m
	SL-16125016	50 cm	141 m	1700 m
2,2 lt/h	SL-16121522	15 cm	54 m	1700 m
	SL-16122022	20 cm	65 m	1700 m
	SL-16122522	25 cm	77 m	1700 m
	SL-16123022	30 cm	87 m	1700 m
	SL-16124022	40 cm	107 m	1700 m
	SL-16125022	50 cm	124 m	1700 m
3,5 lt/h	SL-16121535	15 cm	36 m	1700 m
	SL-16122035	20 cm	44 m	1700 m
	SL-16122535	25 cm	52 m	1700 m
	SL-16123035	30 cm	59 m	1700 m
	SL-16124035	40 cm	72 m	1700 m
	SL-16125035	50 cm	84 m	1700 m

Maximum working pressure: **1,5 Bar**
Recommended Filtration 130 Micron-120 Mesh

Dia 16 mm / 16 mil / 0,40 mm

Flow Rate	Code	Emitter Spacing	Maximum Length	Roll Length
1,6 lt/h	SL-16161516	15 cm	60 m	1300 m
	SL-16162016	20 cm	74 m	1300 m
	SL-16162516	25 cm	87 m	1300 m
	SL-16163016	30 cm	100 m	1300 m
	SL-16164016	40 cm	121 m	1300 m
	SL-16165016	50 cm	141 m	1300 m
2,2 lt/h	SL-16161522	15 cm	54 m	1300 m
	SL-16162022	20 cm	65 m	1300 m
	SL-16162522	25 cm	77 m	1300 m
	SL-16163022	30 cm	87 m	1300 m
	SL-16164022	40 cm	107 m	1300 m
	SL-16165022	50 cm	124 m	1300 m
3,5 lt/h	SL-16161535	15 cm	36 m	1300 m
	SL-16162035	20 cm	44 m	1300 m
	SL-16162535	25 cm	52 m	1300 m
	SL-16163035	30 cm	59 m	1300 m
	SL-16164035	40 cm	72 m	1300 m
	SL-16165035	50 cm	84 m	1300 m

Maximum working pressure: **1,6 Bar**
Recommended Filtration 130 Micron-120 Mesh

Dia 22 mm / 8 mil / 0,20 mm

Flow Rate	Code	Emitter Spacing	Maximum Length	Roll Length
1,6 lt/h	SL-22082016	20 cm	130 m	1750 m
	SL-22083016	30 cm	175 m	1750 m
	SL-22084016	40 cm	215 m	1750 m
2,2 lt/h	SL-22082022	20 cm	114 m	1750 m
	SL-22083022	30 cm	154 m	1750 m
	SL-22084022	40 cm	190 m	1750 m
3,5 lt/h	SL-22082035	20 cm	74 m	1750 m
	SL-22083035	30 cm	87 m	1750 m
	SL-22084035	40 cm	100 m	1750 m

Maximum working pressure: **1,0 Bar**
Recommended Filtration 130 Micron-120 Mesh

Dia 22 mm / 12 mil / 0,30 mm

Flow Rate	Code	Emitter Spacing	Maximum Length	Roll Length
1,6 lt/h	SL-22122016	20 cm	130 m	1200 m
	SL-22123016	30 cm	175 m	1200 m
	SL-22124016	40 cm	215 m	1200 m
2,2 lt/h	SL-22122022	20 cm	114 m	1200 m
	SL-22123022	30 cm	154 m	1200 m
	SL-22124022	40 cm	190 m	1200 m
3,5 lt/h	SL-22122035	20 cm	74 m	1200 m
	SL-22123035	30 cm	87 m	1200 m
	SL-22124035	40 cm	100 m	1200 m

Maximum working pressure: **1,3 Bar**
Recommended Filtration 130 Micron-120 Mesh

Dia 22 mm / 10 mil / 0,25 mm

Flow Rate	Code	Emitter Spacing	Maximum Length	Roll Length
1,6 lt/h	SL-22102016	20 cm	130 m	1500 m
	SL-22103016	30 cm	175 m	1500 m
	SL-22104016	40 cm	215 m	1500 m
2,2 lt/h	SL-22102022	20 cm	114 m	1500 m
	SL-22103022	30 cm	154 m	1500 m
	SL-22104022	40 cm	190 m	1500 m
3,5 lt/h	SL-22102035	20 cm	74 m	1500 m
	SL-22103035	30 cm	87 m	1500 m
	SL-22104035	40 cm	100 m	1500 m

Maximum working pressure: **1,1 Bar**
Recommended Filtration 130 Micron-120 Mesh

Dia 25 mm / 12 mil / 0,30 mm

Flow Rate	Code	Emitter Spacing	Maximum Length	Roll Length
1,6 lt/h	SL-25122016	20 cm	220 m	1000 m
	SL-25123016	30 cm	274 m	1000 m
	SL-25124016	40 cm	330 m	1000 m
2,2 lt/h	SL-25122022	20 cm	200 m	1000 m
	SL-25123022	30 cm	254 m	1000 m
	SL-25124022	40 cm	310 m	1000 m
3,5 lt/h	SL-25122035	20 cm	74 m	1000 m
	SL-25123035	30 cm	87 m	1000 m
	SL-25124035	40 cm	100 m	1000 m

Maximum working pressure: **1,0 Bar**
Recommended Filtration 130 Micron-120 Mesh

